

Best Available Copy

Patent Application of  
Oral F. Sekendur  
For

One-Piece Disposable Dental Articulator

Field of Invention

This invention relates to a one-piece disposable dental articulator. It is formed in one piece from a single sheet of plastic whereby the upper and lower quadrants are stamped perpendicular to the vertical length of the one-piece disposable dental articulator to form the two hinged ends and a body member. The hinges allow the upper and lower members free radial motion about the axis of the stamped hinges and they are able to fold flush against the body member. On either side of the two hinges are retention holes to secure the articulated dental models.



### Description of Prior Art

The following United States Patents are most closely related to the present invention:

5,026,279	Jun., 1991	Wilkes	433/60.
5,045,949	Sep., 1991	Richardson	433/57.
5,076,786	Dec., 1991	Callne	433/60.
5,141,433	Aug., 1992	Peterson	433/64.
5,221,203	Jun., 1993	Callne	433/58.
5,360,337	Nov., 1994	Westdyk	433/54.
5,425,636	Jun., 1995	Ghim	433/64.
5,622,497	Apr., 1997	Cho	433/60.
5,769,634	Jun., 1998	Choi	433/64.
5,957,688	Sept. 1999	Van Valey	433/60

### Foreign Patent Documents

572850	Nov., 1958	BE	433/64.
1 193 122	Sep., 1985	CA.	
1124255	Oct., 1956	FR	433/54.
446682	Jun., 1927	DE	433/58.
596232	Dec., 1947	GB	433/62.
2098070	Nov., 1982	GB.	

Dental articulators are too complicated and have too many parts. The dental professional needs something that will do the job simply and easily. As the complexity increases, the cost increases. More parts means more parts to break and more things to go wrong. A

1 simple yet versatile one-piece disposable dental articulator that does the job will save  
2 time and money.

3  
4 An excellent background description of disposable articulators is contained in U.S. Patent  
5 5,957,688. Although ingenious, the articulator described in U.S. Patent 5,957,688 is still  
6 too complicated, and has many drawbacks including the time and skill required to  
7 articulate dental models. For example, channels have to be prepared and the articulator  
8 has to be glued in place to these channels. Additionally, this articulator does not have  
9 vertical stops.

10  
11 The present invention overcomes the disadvantages and provides benefits not foreseen in  
12 the prior art by combining simplicity and functionality in a convenient economical  
13 format. It allows quick and easy articulation of dental models so that the dental  
14 professional can focus on making the dental restoration.

### 15 16 17 **Objects and Advantages**

18  
19 It is an object of the present invention to provide a one-piece disposable dental  
20 articulator.

21  
22 It is an object of the present invention to provide a one-piece disposable dental articulator  
23 that allows for lateral and protrusive translatory movement.

24  
25 It is an object of the present invention to provide a one-piece disposable dental articulator  
26 that allows quick and easy articulation of dental models.

27  
28 It is an object of the present invention to provide a one-piece disposable dental articulator  
29 that saves time.

30

1 It is an object of the present invention to provide a one-piece disposable dental articulator  
2 that is economical.

4 It is an object of the present invention to provide a one-piece disposable dental articulator  
5 that easy to use.

7 It is an object of the present invention to provide a one-piece disposable dental articulator  
8 that is functional.

10 It is an object of the present invention to provide a one-piece disposable dental articulator  
11 that is versatile.

13 It is an object of the present invention to provide a one-piece disposable dental articulator  
14 that has many configurations.

16 It is an object of the present invention to provide a one-piece disposable dental articulator  
17 that can be used for fixed prosthetics.

19 It is an object of the present invention to provide a one-piece disposable dental articulator  
20 that can be used for removable prosthetics.

22 It is an object of the present invention to provide a one-piece disposable dental articulator  
23 that has accurate and adjustable vertical stops.

#### 26 Description of Drawings

is a perspective view of an embodiment having a body member with two  
hinged ends.

are side views of various embodiments of the dental articulator.

- 1 Fig. 3 is a perspective view of an embodiment having an upper screw and a  
 2 lower screw.  
 3 Fig. 4 is a perspective view of an embodiment having mounting plates.  
 4 Fig. 5 is a side view of an embodiment having short retention pins or long  
 5 retention pins.  
 6 Fig. 6a-6 are side views of various embodiments of the one-piece disposable dental  
 7 articulator with mounting plates.  
 8 Fig. 7 is a side view of an embodiment comprising an "L" shaped lower body  
 9 member.  
 10 Fig. 8 is a side view of an embodiment comprising an "L" shaped lower body  
 11 member comprising retention holes and an upper screw.  
 12  
 13  
 14  
 15

**Reference: Numerals in Drawing**

1	dental articulator	2	body member
3	upper member	4	lower member
5	upper hinge	6	lower hinge
7	upper body retention holes	8	lower body retention holes
9	upper member retention holes	10	lower member retention holes
11	upper articulated model	12	lower articulated model
13	upper screw	14	lower screw
15	mounting plates	16	short retention pins
17	long retention pins	18	retention grid
19	"L" shaped lower body member	20	passive vertical stop
21	vertical lower body retention holes	22	horizontal lower body retention holes

## **Description of Preferred Embodiments**

The present invention uses a one-piece disposable dental articulator 1 in Fig. 1 constructed in one-piece from a single sheet of plastic that is stamped perpendicular to the vertical length of the one-piece disposable dental articulator at the upper and lower quadrants between a body member 2 and an upper member 3 to form an upper hinge 5, and between the body member and a lower member 4 to form a lower hinge 6. The hinges allow the upper and lower members free radial motion about the axis of the stamped hinges and they are able to fold flush against the body member. On either side of the two hinges are upper body retention holes 7, lower body retention holes 8, upper member retention holes 9 and lower member retention holes 10 to hold articulated models.

The one-piece disposable dental articulator is sufficiently resilient to allow for transverse motion along the vertical axis of the body member when sufficient force is applied in the direction of the desired motion. This allows for sufficient lateral and protrusive translatable motions and simulates occlusal and masticatory motions between the articulated models.

Accordingly, several alternative configurations of articulating models are possible as shown in Figs. 2a-2d. In Fig. 2a, said upper member and said lower member are extended approximately perpendicular to said body member. The retention holes secure the models in position. This configuration gives the dental professional a choice of using the upper hinge or lower hinge axis. The upper hinge is used by breaching the connection at the upper body retention holes to allow free movement of the upper hinge. Alternatively, the lower hinge can be used by breaching the connection at the lower body retention holes to allow free movement of the lower hinge.

Since the upper member and lower member are capable of folding flush against the body member, other configurations of articulating models are possible by folding either the upper member Fig. 2b, lower member Fig. 2c or both upper member and lower member

Fig. 2d flush against the body member. In the flush position, two sets of retention holes secure the articulated models in position. The upper body retention holes and upper member retention holes are one set and the lower body retention and the lower member retention holes are the other set. Again, either hinge axis can be used. The upper hinge is used by breaching the connection at the upper body retention holes to allow free movement of the upper hinge. The lower hinge can be used by breaching the connection at the lower body retention holes to allow free movement of the lower hinge.

The configurations in Figs. 2a-2d, comprise a passive vertical stop 20 when the upper articulated model 11 or lower articulated model 12 comes to rest flush against the body member preventing further movement along the upper hinge or lower hinge axis in the direction of the body member.

In another embodiment, adjustable vertical stops use an upper screw 13 in Fig. 3 and a lower screw 14 to force the upper articulated model or lower articulated model away from the body member to the desired position.

In a further embodiment, mounting plates 15 in Fig. 4 are provided comprising short retention pins 16 in Fig. 5 or long retention pins 17 on one side and a retention grid 18 in Fig. 4 on the other side. The retention grid secures the dental model to the mounting plate. The mounting plates are fixed on the one-piece disposable dental articulator in various configurations by fitting the retention pins into the retention holes in the desired configuration. The long retention pins are used with the upper member or the lower member in the folded position to secure to the retention pins to the upper body retention holes or the lower body retention holes of the body member and maintain the folded position whereby the long retention pins pass through the upper member or the lower member. Some of the many configurations include fitting the retention pins to the various retention holes with the upper member or the lower member in the folded or unfolded position as illustrated in Figs. 6a-6g.

1 Among the many configurations include: a) at least one mounting plate is fixed on the  
2 upper member retention holes and the lower member retention holes whereby the upper  
3 member and the lower member are extended approximately perpendicular to the body  
4 member, b) at least one mounting plate is fixed on the upper member retention holes  
5 whereby the upper member and the lower member are extended approximately  
6 perpendicular to the body member, c) at least one mounting plate fixed on the lower  
7 member retention holes whereby the upper member and the lower member are extended  
8 approximately perpendicular to the body member, d) at least one mounting plate is fixed  
9 on the upper body retention holes whereby the upper member and the lower member are  
10 extended approximately perpendicular to the body member, e) at least one mounting plate  
11 is fixed on the lower body retention holes whereby the upper member and the lower  
12 member are extended approximately perpendicular to the body member, f) at least one  
13 mounting plate is fixed on the outside surface of the upper member folded flush against  
14 the body member, g) at least one mounting plate is fixed on the outside surface of the  
15 lower member folded flush against the body member, and h) at least one mounting plate  
16 is fixed on the outside surface of the upper member folded flush against the body member  
17 and the lower member folded flush against the body member.

18  
19 A still further embodiment comprises an "L" shaped lower body member 19 in Fig. 7 and  
20 an upper hinge 5, whereby the only moving part is the upper hinge, and whereby the "L"  
21 shaped lower body member comprises a single solid piece. The one-piece disposable  
22 dental articulator is stamped perpendicular to its vertical length at the upper quadrant  
23 between the "L" shaped lower body member and the upper member to form the upper  
24 hinge thereby allowing free radial motion about the axis of the upper hinge. This  
25 embodiment further comprises upper member retention holes 9 in Fig. 8 for securing an  
26 upper articulated model, upper body retention holes 7 for securing an upper articulated  
27 model, vertical lower body retention holes 21 for securing a lower articulated model, and  
28 horizontal lower body retention holes 22 for securing a lower articulated model. An  
29 upper screw 13 is provided.



1 Further, the one-piece disposable dental articulator in this embodiment is sufficiently  
2 resilient to allow for transverse motion along the vertical axis of the "L" shaped lower  
3 body member when sufficient force is applied in the direction of the desired motion to  
4 allow for sufficient lateral and protrusive translatory motions and to simulate occlusal and  
5 masticatory motions.

6  
7 Other embodiments include a one-piece disposable dental articulator made of metal,  
8 plastic, composite, metal with stamped hinges, plastic with stamped hinges, composite  
9 with stamped hinges, metal with conventional hinges, plastic with conventional hinges  
10 and composite with conventional hinges.

11  
12 The one-piece disposable dental articulator embodiments described herein are capable of  
13 being manufactured inexpensively by forming them from a single sheet of plastic without  
14 the use of costly molds or casts.

15  
16 The invention is not in any way strictly limited to the examples of construction described  
17 previously, but encompasses numerous embodiments, modifications and improvements.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**